



LOCAL PLANNING SCHEME NO. 10

LOCAL PLANNING POLICY NO. 6 INDUSTRIAL ZONES DEVELOPMENT DESIGN GUIDELINES

OBJECTIVE

To ensure that a high standard of industrial development, in terms of appearance, landscaping, provision of parking and access.

APPLICATION

This policy applies to all the land zoned 'Light Industrial' and 'General Industrial' under Local Planning Scheme No. 10.

POLICY

All development within the 'Light Industrial' and 'General Industrial' zones shall comply with the following requirements:

Building Setbacks

The minimum setback requirements for all buildings within these zones shall be in accordance with those prescribed as follows:

Front	14.00m
Rear	5.00m
Side	4.50m one side
Secondary Street	7.00m

Vehicle parking

Car parking spaces shall be provided, constructed and maintained in accordance with the provisions of Part 5 of the Scheme, Local Planning Scheme Policy No. 8 (Parking Specifications) and the approved plan relating thereto.

Landscaping

All development within these zones shall be landscaped in accordance with the following requirements

- a) the minimum width of front boundary landscaping shall be 3 metres, except in the case of a corner lot, in which case the minimum shall be 1.5 metres on the secondary street as nominated by Council;
- b) the minimum width of side boundary landscaping (excluding side street boundaries) shall be 1 metre, to be provided from the front boundary to the setback line;
- c) landscaping is to be provided in accordance with Councils landscaping policy as amended from time to time, and shall be maintained by the owner of the lot thereafter.
- d) Shade trees in car parking areas shall be provided at a ratio of 1 per six car parking bays recommended in the Councils' landscaping policy.

Security Fencing

Where a security fence is proposed on a street lot boundary, it shall be of an open style either mesh fencing.

Solid screen fences on industrial sites are only acceptable where located at or behind the 14-metre building line to the front setback area. In the case of corner lots solid screen fencing must be setback 7-metres from the secondary street.

Service Access

Provision shall be made for service access in the following manner:

- a) a paved accessway shall be provided for vehicles from the street to the rear of and to any other part of the building where provision is made in the external walls of the building for the entry of or the loading or unloading of vehicles;
- b) the access way shall be so constructed that all vehicles using it can enter from and return to a street in forward gear without reversing any part of the vehicle onto a street; and
- c) except as hereinafter mentioned, the access way shall not be less than 4.5 metres in width, unless the size of the lot makes the provision of such an access way impracticable or unreasonable the Council may permit an access way of a narrower width but in no case less than 3.0 metres in width.

Storage and Refuse areas

The Council may require the provision of one or more areas for the storage of refuse in a development. This area shall be:

- a) screened from view from any public street, and enclosed by a wall of masonry or other approved building material, and being of not less than 1.8 metres in height; and
- b) accessible to service vehicles.

Irrespective of whether a storage area is required for a development, no land shall be used for open storage purposes unless it is screened from view of any public street by a fence or wall built to the specifications and satisfaction of the Council.

Building Materials

The facades of all buildings facing public streets shall be constructed of brick, glass, stone, masonry or concrete in respect of the ground floor level. The second floor level, or its equivalent, may be constructed of other material in accordance with the Building Code of Australia.

The use of zincalume sheeting for construction of Industrial buildings is prohibited, unless such buildings or parts of buildings are not visible from any public street, or Council approval is granted to vary this requirement.

Floor Area

A factory or factory unit shall have a floor area of not less than 100m² and each the length and width shall not be less than 6 metres clear between the internal wall surfaces.

Factory Units

Multiple factory units on one lot shall not be permitted unless the following requirements are complied with:

- a) each factory unit shall have a visually screened service yard of not less than 16m² with a minimum depth of 2m adjoining and having connecting access to each unit; and
- b) the internal partition walls between factory units shall be constructed of brick, stone or concrete or other material approved by Council.